

**Technical Data Sheet**

**CYPRESS OIL - CYPRE0001**

Reference : CYPRESS OIL - CYPRE0001

**TECHNICAL DATA**

Relative density (d20/20) : [0.863 ; 0.885]  
 Refractive index at 20°C : [1.468 ; 1.478]  
 Angular rotation (°) : [+15 ; +30]  
 Color : pale yellow to yellow  
 Appearance : liquid  
 Odor : woody, turpentine, rustic  
 Flash point : 35° C  
 I.N.C.I : CUPRESSUS SEMPERVIRENS LEAF EXTRACT  
 Manufacturing process : obtained by steam distillation of the leaves and branches of Cupressus sempervirens L.  
 hydrocarbons content : 90%





**TRANSPORT-STORAGE**

Custom tariff : 33012941  
 STORAGE CONDITIONS : Store product in full, tightly closed containers

**LEGISLATION :**

COE : 162n  
 EINECS : 283-626-9  
 C.A.S : 8013-86-3 84696-07-1

**Labeling :**

 AH1 Aspiration hazard 1  
 EHC2 Hazardous to the aquatic environment, long-term hazard 2  
 FL3 Flammable Liquids 3  
 SS1 Sensitisation skin 1

H226 - Flammable liquid and vapour.  
 H304 - May be fatal if swallowed and enters airways.  
 H316 - Causes mild skin irritation  
 H317 - May cause an allergic skin reaction.  
 H401 - Toxic to aquatic life  
 H411 - Toxic to aquatic life with long lasting effects.

P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
 P233 - Keep container tightly closed.  
 P241 - Use explosion-proof electrical/ventilating/lighting/.../equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge  
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P272 - Contaminated work clothing should not be allowed out of the workplace.  
 P273 - Avoid release to the environment.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.